


























ITEM	SIZE	POWR	PIC	SPE	CCT	INPUT	LM/W	COVER	UL TYPE		DLC NO.	MODEL	Re		
1	4FT	10W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PR6WKE24	WL-T8A-10W1200 DIAB	HYBRID T8 TUBES ALU+PC		
					4500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PTXH7J1E				
					3500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PI2G3G5Z				
					4000K	100-277Vac	130	Frosted/Clear	A+B	All in one	P796SMC3				
2	4FT	12W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PU9J1O2D	WL-T8A-12W1200 DIAB		HYBRID T8 TUBES ALU+PC	
					4000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PF4R3H1I				
					4500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PBZ76BHE				
					3000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PQ800R5A				
3	4FT	15W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	130	Frosted/Clear	A+B	All in one	P6XUVJW0	WL-T8A-15W1200 DIAB			HYBRID T8 TUBES ALU+PC
					4000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PB3GHFU4				
					4500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PI1RXS6G				
					3000K	100-277Vac	130	Frosted/Clear	A+B	All in one	P1KNLL2A				
4	4FT	18W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	130	Frosted/Clear	A+B	All in one	P0U36VZB	WL-T8A-18W1200 DIAB			
					4000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PEK8QGQB				
					4500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PV4OADRA				
					3500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PJ899R3E				
5	4FT	22W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PXYRMCQH	WL-T8A-22W1200 DIAB	HYBRID T8 TUBES ALU+PC		
					4500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PLP0VFGB				
					3500K	100-277Vac	130	Frosted/Clear	A+B	All in one	PQR3ECYQ				
					4000K	100-277Vac	130	Frosted/Clear	A+B	All in one	PJLRV3HS				
6	4FT	10W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日	WL-T8A-10W600 DIAB-H		HYBRID T8 TUBES ALU+PC	
					4000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					3000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
7	4FT	12W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日	WL-T8A-12W1200 DIAB-H			HYBRID T8 TUBES ALU+PC
					4000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					3000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
8	4FT	15W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日	WL-T8A-15W1200 DIAB-H			
					4000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					3000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
9	4FT	18W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日	WL-T8A-18W1200 DIAB-H	HYBRID T8 TUBES ALU+PC		
					4000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					3000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
10	4FT	22W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日	WL-T8A-22W1200 DIAB-H		HYBRID T8 TUBES ALU+PC	
					4000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					3000K	100-277Vac	150	Frosted/Clear	A+B	All in one	8月10日				
					5000K	100-277Vac	130	Frosted	A+B	All in one	P8Y84FS1				
11	4FT	10W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	4500K	100-277Vac	130	Frosted	A+B	All in one	P7YOWXVF	WL-T8N-10W1200 DIAB			HYBRID TUBE NANO PLASTIC
					3500K	100-277Vac	130	Frosted	A+B	All in one	PYCCN6QP				
					4000K	100-277Vac	130	Frosted	A+B	All in one	PZTMK80F				
					5000K	100-277Vac	130	Frosted	A+B	All in one	PZCPQT2G				
12	4FT	12W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	4500K	100-277Vac	130	Frosted	A+B	All in one	P00HM298	WL-T8N-12W1200 DIAB			
					3500K	100-277Vac	130	Frosted	A+B	All in one	PCVWO6HO				
					4000K	100-277Vac	130	Frosted	A+B	All in one	P2ERI633				
					3000K	100-277Vac	130	Frosted	A+B	All in one	PSGQLEZP				
13	4FT	15W		Ballast Compatible T8 LED Internal driver Ra83 50,000hrs cULus - E477861	5000K	100-277Vac	130	Frosted	A+B	All in one	P8VMV2AH	WL-T8N-15W1200 DIAB	HYBRID TUBE NANO PLASTIC		
					4500K	100-277Vac	130	Frosted	A+B	All in one	PLTIDA8H				
					3500K	100-277Vac	130	Frosted	A+B	All in one	PFB3JNPT				
					4000K	100-277Vac	130	Frosted	A+B	All in one	PRY5RKR9				

ITEM	SIZE	POWR	PIC	SPE	CCT	INPUT	LM/W	COVER	UL TYPE		DLC NO.	MODEL	Re
14	4FT	10W		T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted/Clear	B	Single / Double	PMSFTPJE	FL-T8-10W600 BISS	VOLTAGE T8 TUBE ALU+PC
					4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	PN8HHRJF		
					3500k	100-277Vac	130	Frosted/Clear	B	Single / Double	PQBHACEX		
					4000K	100-277Vac	130	Frosted/Clear	B	Single / Double	PV4ET8W5		
15	4FT	12W		T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted/Clear	B	Single / Double	PFW2684D	FL-T8-12W1200 BISS	
					4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	PJQ2RYRE		
					4000k	100-277Vac	130	Frosted/Clear	B	Single / Double	PBA35TKR	FL-T8-12W1200 BIDS	
					5000k	100-277Vac	130	Frosted/Clear	B	Single / Double	PU2GR91V		
					4500K	100-277Vac	130	Frosted/Clear	B	Single / Double	PJ88MJ1P		
					4000K	100-277Vac	130	Frosted/Clear	B	Single / Double	PZF6SQAA		
16	4FT	15W		T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted/Clear	B	Single / Double	PQ8NAJUC	FL-T8-15W1200 BISS	
					4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	PUYMD3PY		
					4000k	100-277Vac	130	Frosted/Clear	B	Single / Double	PUKEMMPK	FL-T8-15W1200 BIDS	
					5000k	100-277Vac	130	Frosted/Clear	B	Single / Double	P1HSQ6M8		
					4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	PRZDA1QN		
17	4FT	18W		T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted/Clear	B	Single / Double	P9HFYCVY	FL-T8-18W1200 BISS	
			4500k		100-277Vac	130	Frosted/Clear	B	Single / Double	PQNZ2CP3			
			4000k		100-277Vac	130	Frosted/Clear	B	Single / Double	PAPWGD2E	FL-T8-18W1200 BIDS		
			5000k		100-277Vac	130	Frosted/Clear	B	Single / Double	PHJA3WXT			
18	4FT	22W	T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted/Clear	B	Single / Double	PZ7NEJAA	FL-T8-22W1200 BISS		
				4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	P38MK4FD			
				4000k	100-277Vac	130	Frosted/Clear	B	Single / Double	PCR6TUW	FL-T8-18W1200 BIDS		
				5000k	100-277Vac	130	Frosted/Clear	B	Single / Double	P9C6BYKN			
				4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	P9N4F13B			
				4000k	100-277Vac	130	Frosted/Clear	B	Single / Double	PW8GHEJ5			
19	8FT	40W	T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000k	100-277Vac	130	Frosted/Clear	B	Single / Double	P8MQ5TRY	FL-T8-40W2400 BIDS		
				4500k	100-277Vac	130	Frosted/Clear	B	Single / Double	P2C1IK06			
				4000k	100-277Vac	130	Frosted/Clear	B	Single / Double	PLIAPVBC			
20	4FT	10W	T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted	B	Single / Double	PYX8PQT7	WL-T8N-10W1200 BISS WL-T8N-10W1200 BIDS		
				4500k	100-277Vac	130	Frosted	B	Single / Double	PISCOR78			
				4000k	100-277Vac	130	Frosted	B	Single / Double	P9QBYSTY			
				3500k	100-277Vac	130	Frosted	B	Single / Double	PRA8JOXJ			
21	4FT	12W	T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted	B	Single / Double	PL9EUX28	WL-T8N-12W1200 BISS WL-T8N-12W1200 BIDS		
				4500K	100-277Vac	130	Frosted	B	Single / Double	PYTISGYN			
				4000k	100-277Vac	130	Frosted	B	Single / Double	P13FQH10			
				3500k	100-277Vac	130	Frosted	B	Single / Double	PW6VJWSJ			
				3000K	100-277Vac	130	Frosted	B	Single / Double	PXL3SG4D			
22	4FT	15W	T8 LED Internal driver SMD2835 Ra83 50,000hrs cULus - E477860	5000K	100-277Vac	130	Frosted	B	Single / Double	PITU9X8V	WL-T8N-15W1200 BISS WL-T8N-15W1200 BIDS		
				4500k	100-277Vac	130	Frosted	B	Single / Double	P6IVRG3M			
				4000K	100-277Vac	130	Frosted	B	Single / Double	PI148PRM			
				3500k	100-277Vac	130	Frosted	B	Single / Double	PXRCGC14			
				3000K	100-277Vac	130	Frosted	B	Single / Double	PP1GZXM9			

ITEM	SIZE	POWR	PIC	SPE	CCT	INPUT	LM/W	COVER	UL TYPE		DLC NO.	MODEL	Re
23	4FT	10W		Ballast Compatible T8 LED I External driver I SMD2835 I Ra83 I 50,000hrs I cULus	4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PQTLTCRU	WL-M-10W1200 NW-2	MAGNETIC LINEAR RETROFIT KIT
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	P0NZH4O1	WL-M-10W1200 NW-3	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PCJGEZWE	WL-M-10W1200 NW-4	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PY9MNYD2	WL-M-10W1200 CW-2	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PILLUT435	WL-M-10W1200 CW-3	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PFN5PG8N	WL-M-10W1200 CW-4	
24	4FT	12W		Ballast Compatible T8 LED I External driver I SMD2835 I Ra83 I 50,000hrs I cULus	4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	P8ZKNV1D	WL-M-12W1200 NW-2	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PGD6WH5U	WL-M-12W1200 NW-3	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PBQ6JOKA	WL-M-12W1200 NW-4	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PK9O4TQD	WL-M-12W1200 CW-2	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PC53Z7BM	WL-M-12W1200 CW-3	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PPUILAVW	WL-M-12W1200 CW-4	
25	4FT	15W		Ballast Compatible T8 LED I External driver I SMD2835 I Ra83 I 50,000hrs I cULus	4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PSVYWUW4	WL-M-15W1200 NW-2	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PCM2A81I	WL-M-15W1200 NW-3	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	P8QE8M81	WL-M-15W1200 NW-4	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PLGX95I4	WL-M-15W1200 CW-2	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PC8GHOLE	WL-M-15W1200 CW-3	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PQ865M6O	WL-M-15W1200 CW-4	
26	4FT	18W		Ballast Compatible T8 LED I External driver I SMD2835 I Ra83 I 50,000hrs I cULus	4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PWQCHV1V	WL-M-18W1200 NW-2	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PARA3RP8	WL-M-18W1200 NW-3	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PB6KB3AF	WL-M-18W1200 CW-2	
					5000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PQ52AFBC	WL-M-18W1200 CW-3	
27	4FT	10W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	PP5SDJA3	WL-T8-10W1200 BODA-2-35	TUBE WITH EXTERNAL DRIVER PLU+PC
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	PMNDJZS1	WL-T8-10W1200 BODA-3-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 4	P5SQ9SXX	WL-T8-10W1200 BODA-4-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PO0679CW	WL-T8-10W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PR65SISR	WL-T8-10W1200 BODA-3-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PUENU7SF	WL-T8-10W1200 BODA-4-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	P0F8O87A	WL-T8-10W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PTK1D0EL	WL-T8-10W1200 BODA-3-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 4	PYYOVT4P	WL-T8-10W1200 BODA-4-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	PR1MJHJ	WL-T8-10W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PFJ0EPLO	WL-T8-10W1200 BODA-3-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 4	PM7WYT2M	WL-T8-10W1200 BODA-4-50	
28	4FT	12W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	PWACGMCT	WL-T8-12W1200 BODA-2-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	PUBRLIV	WL-T8-12W1200 BODA-3-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 4	PSP04NCI	WL-T8-12W1200 BODA-4-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PDNCEZ7B	WL-T8-12W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	P1Y715Y7	WL-T8-12W1200 BODA-3-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	P6R1GQ2W	WL-T8-12W1200 BODA-4-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	PES4BB4J	WL-T8-12W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PSMN12GR	WL-T8-12W1200 BODA-3-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 4	PQ7NMQ8Y	WL-T8-12W1200 BODA-4-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	P59R6X4D	WL-T8-12W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PW6XDUD1	WL-T8-12W1200 BODA-3-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 4	PNL2G1BR	WL-T8-12W1200 BODA-4-50	
29	4FT	15W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	P72A0L8T	WL-T8-15W1200 BODA-2-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	PP9LYN9	WL-T8-15W1200 BODA-3-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 4	PNUJPQRN	WL-T8-15W1200 BODA-4-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PJM5AAH5	WL-T8-15W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	P5OIZT1Z	WL-T8-15W1200 BODA-3-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PPWPHHY8	WL-T8-15W1200 BODA-4-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	PZN5TK0F	WL-T8-15W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	P3TAUTCX	WL-T8-15W1200 BODA-3-45	
4500K	120-277Vac	135	Frosted	C	External driver 1 by 4	P4QILUEE	WL-T8-15W1200 BODA-4-45						

ITEM	SIZE	POWR	PIC	SPE	CCT	INPUT	LM/W	COVER	UL TYPE	DLC NO.	MODEL	Re	
30	4FT	18W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	P096O3GA	WL-T8-15W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PH3VZBC1	WL-T8-15W1200 BODA-3-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 4	PQAR3XRX	WL-T8-15W1200 BODA-4-50	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	PY1YXANX	WL-T8-18W1200 BODA-2-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	P7QE8IH0	WL-T8-18W1200 BODA-3-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	P99KSV58	WL-T8-18W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PNOSG01U	WL-T8-18W1200 BODA-3-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	P7M3IX5V	WL-T8-18W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PV8ZJOWD	WL-T8-18W1200 BODA-3-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	PF176J6Q	WL-T8-18W1200 BODA-2-50	
5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PVMLGW54	WL-T8-18W1200 BODA-3-50						
31	4FT	10W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	PG7ZY2G8	WL-T8-10W1200 BODA-2-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	PSKZ1NUM	WL-T8-10W1200 BODA-3-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 4	PW94KGLH	WL-T8-10W1200 BODA-4-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PSAVNSGW	WL-T8-10W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PZT5H0YC	WL-T8-10W1200 BODA-3-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	PKEVAQWO	WL-T8-10W1200 BODA-4-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	PTRHCZ89	WL-T8-10W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PNATZY42	WL-T8-10W1200 BODA-3-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 4	PADSF7SU	WL-T8-10W1200 BODA-4-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	PA2P1U1U	WL-T8-10W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	P3QUMDAE	WL-T8-10W1200 BODA-3-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 4	PFE7UF7P	WL-T8-10W1200 BODA-4-50	
32	4FT	12W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	P9351VES	WL-T8-12W1200 BODA-2-35	TUBE WITH EXTERNAL DRIVER NANO
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	P3W698VI	WL-T8-12W1200 BODA-3-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 4	PIF14YH9	WL-T8-12W1200 BODA-4-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PT0N3NG6	WL-T8-12W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PPZT4LYO	WL-T8-12W1200 BODA-3-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	P2NEU4GT	WL-T8-12W1200 BODA-4-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	PF7K8UH	WL-T8-12W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PSRVQ2ZD	WL-T8-12W1200 BODA-3-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 4	PC8X7Z0M	WL-T8-12W1200 BODA-4-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	PHACZVY9	WL-T8-12W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PRQG4KX0	WL-T8-12W1200 BODA-3-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 4	P1HEMOMF	WL-T8-12W1200 BODA-4-50	
33	4FT	15W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	PZA8X8Z5	WL-T8-15W1200 BODA-2-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	P6O0KDC7	WL-T8-15W1200 BODA-3-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 4	P2O0UVA1	WL-T8-15W1200 BODA-4-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	PGXZXPQA	WL-T8-15W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	PWHOW20C	WL-T8-15W1200 BODA-3-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 4	P129IVWY	WL-T8-15W1200 BODA-4-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	PHW9PA6Y	WL-T8-15W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PPWRB1VI	WL-T8-15W1200 BODA-3-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 4	PVRD4O3C	WL-T8-15W1200 BODA-4-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	PNPX0WD5	WL-T8-15W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PW0TTA7H	WL-T8-15W1200 BODA-3-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 4	PLVPSDHY	WL-T8-15W1200 BODA-4-50	
34	4FT	18W		Ballast Compatible T8 LED I External driver I Ra83 I 50,000hrs I cULus	3500k	120-277Vac	135	Frosted	C	External driver 1 by 2	PBORNZRE	WL-T8-18W1200 BODA-2-35	
					3500k	120-277Vac	135	Frosted	C	External driver 1 by 3	P3HG2EUI	WL-T8-18W1200 BODA-3-35	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 2	P0ZILLU08	WL-T8-18W1200 BODA-2-40	
					4000K	120-277Vac	135	Frosted	C	External driver 1 by 3	P7S02C80	WL-T8-18W1200 BODA-3-40	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 2	PDN8FNMR	WL-T8-18W1200 BODA-2-45	
					4500K	120-277Vac	135	Frosted	C	External driver 1 by 3	PV1VM3TK	WL-T8-18W1200 BODA-3-45	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 2	P7EM1FT0	WL-T8-18W1200 BODA-2-50	
					5000K	100-277Vac	135	Frosted	C	External driver 1 by 3	PAMIR9AR	WL-T8-18W1200 BODA-3-50	

ITEM	SIZE	POWR	PIC	SPE	CCT	INPUT	LM/W	COVER	UL TYPE	DLC NO.	MODEL	Re
35	2FT	35W		LED Troffer Retrofit Kits,130lm/W, AC100-277V, dimmable or non-dimmable, 600*600mm 5 years warranty, ULstandard Form Facto	5000K	100-277Vac	130LPW	Frosted		PBXSKDYI	TL-35W600600-RDCW	
					5000K			Frosted		PQPI8KA9	TL-35W600600-RNCW	
					4000K			Frosted		PANNWR26	TL-35W600600-RNNW	
					4000K			Frosted		P4ZQB8NP	TL-35W600600-RDNW	
36	4FT	50W		LED Troffer Retrofit Kits,130lm/W, AC100-277V, dimmable or non-dimmable, 600*600mm 5 years warranty, ULstandard Form Facto	5000K	100-277Vac	130LPW	Frosted		PYNEGMNN	TL-50W6001200-RDCW	
					5000K			Frosted		P9A2YA0K	L-50W6001200-RNNW	
					4000K			Frosted		PO0GFIVL	TL-50W6001200-RDNW	
					4000K			Frosted		PDHXI2VS	TL-50W6001200-RDCW	
37	1*4 FT	36W		FLAT PANEL LED I AC100-277V 50/60Hz I SMD2835 I Ra83 I 50,000hrs I cULus DLC	4000K	100-277Vac	100LP W			P9XJWEYS	PL-36W3001200-1DNW	
					5000K					PXKF5EQQ	PL-36W3001200-1DCW	
					3000K					P7BX2V6Y	PL-36W3001200-1DWW	
38	2*2 FT	40W		FLAT PANEL LED I AC100-277V 50/60Hz I SMD2835 I Ra83 I 50,000hrs I cULus DLC	3000K	100-277Vac	100LP W			PU41GCPJ	PL-40W600600-2DWW	
					4000K					PYFCH7FB	PL-40W600600-2DNW	
					5000K					PBZA7WMU	PL-40W600600-2DCW	
					4000K		130LP W			PRSH13YN	PL-40W600600-2DNW-H1	
					5000K					PBGNQ3W3	PL-40W600600-2DCW-H1	
39	2*4 FT	52W		FLAT PANEL LED I AC100-277V 50/60Hz I SMD2835 I Ra83 I 50,000hrs I cULus DLC	4000K	100-277Vac	100LP W			PN1WD7TH	PL-52W6001200-2DNW	
					5000K					P1AK7PCR	PL-52W6001200-2DCW	
					4000K		130LP W			PNX3Y1BZ	PL-52W6001200-2DNW-H1	
					5000K					P6HNUKEP	PL-52W6001200-2DCW-H1	
40	2*4 FT	70W		FLAT PANEL LED I AC100-277V 50/60Hz I SMD2835 I Ra83 I 50,000hrs I cULus DLC	4000K	100-277Vac	100LP W			PS66YUN8	PL-70W6001200-2DNW	
					5000K					PYWWUZ3F	PL-70W6001200-2DCW	
41	2 FT	90W		LED Linear Highbay Light,125lm/W, AC100-277V, dimmable, 605*320*95mm, IP Rating: IP44 5 years warranty, UL/Cul/DLC premium Factor:Lenth =2' Lenth =4' Iafared senor optional	4000k	100-277Vac	130LP W			PNRMAKMS	HB-90W320605-L-DNW2	
					5000k					PATGEPUS	HB-90W320605-L-DCW2	
42	2 FT	120W		LED Linear Highbay Light,125lm/W, AC100-277V, dimmable, 605*320*95mm, IP Rating: IP44 5 years warranty, UL/Cul/DLC premium Factor:Lenth =2' Lenth =4' Iafared senor optional	4000K	100-277Vac	130LPW			PMHBZEYV	HB-120W320605-L-DNW2	
					5000K					PAMHQD1Y	HB-120W320605-L-DCW2	
43	2 FT	150W		LED Linear Highbay Light,125lm/W, AC100-277V, dimmable, 605*439*95mm, IP Rating: IP44 5 years warranty, UL/Cul/DLC standard Factor:Lenth =2' Lenth =4' Iafared senor optional	4000k	100-277Vac	130LPW			PDH6WGDY	HB-150W320605-L-DNW2	
					5000k					P4BQQXVT	HB-150W320605-L-DCW2	
44	3 FT	180W		LED Linear Highbay Light,125lm/W, AC100-277V, dimmable, 605*439*95mm, IP Rating: IP44 5 years warranty, UL/Cul/DLC standard Factor:Lenth =2' Lenth =4' Iafared senor optional	4000k	100-277Vac	130LPW			PE9DP37T	HB-180W439605-L-DNW2	
					5000k					P494DSW3	HB-180W439605-L-DCW2	